

Polycom HDX 6000 Series Specifications

Package Includes

- Polycom EagleEye™ or EagleEye View camera, codec, HDX Microphone Array (not with View camera model), 2 Mbps point-to-point, cables and remote control

Video Standards and Protocols

- H.264, H.264 High Profile, H.263++, H.261
- H.239 / Polycom People+Content
- H.263 & H.264 Video Error Concealment

Video Input

- 1 x Polycom EagleEye HD camera
- 1 x DVI-I

Video Output

- 1 x HDMI

People Video Resolution

- 720p, 30 fps from 512 Kbps
- 4SIF/4CIF, 30 fps from 128 Kbps
- 4SIF/4CIF, 60 (RX) fps from 512 Kbps
- SIF (352 x 240), CIF (352 x 288)
- QSIF (176 x 120), QCIF (176 x 144)

Content Video Resolution

- Resolutions supported: WSXGA+ (1680 x 1050), SXGA (1280 x 1024), HD (1280 x 720), XGA (1024 x 768), SVGA (800 x 600), VGA (640 x 480)
- Output: 720p (1280 x 720), 1080 (1920 x 1080), XGA (1024 x 768), SVGA (800 x 600)
- Content Sharing: People+Content™ and People+Content IP

Camera

- Polycom EagleEye camera
 - 1280 x 720p CCD imager
 - 12X optical zoom
 - 72° FOV min
- Polycom EagleEye View camera
 - 1920 x 1080 EPTZ camera
 - 4X digital zoom
 - 55° FOV min
 - Internal stereo microphones

Audio Input

- 1 HDX microphone array supported
- 1 x 3.5 mm stereo mini (PC Audio)

Audio Output

- 1 x Aux main out (RCA)
- Digital audio on HDMI cable



Audio Standards and Protocols

- Polycom StereoSurround™
- 22 kHz bandwidth with Polycom Siren™ 22
- 14 kHz bandwidth with Polycom Siren 14, G.722.1 Annex C
- 7 kHz bandwidth with G.722, G.722.1
- 3.4 kHz bandwidth with G.711, G.728, G.729A
- Automatic gain control
- Automatic noise suppression
- Keyboard noise reduction
- Live music mode
- Instant adaptation echo cancellation
- Audio error concealment

Other ITU-Supported Standards

- H.221, H.224/H.281, H.323 Annex Q, H.225, H.245, H.241, H.331, H.239, H.231, H.243, H.460, BONDING, Mode 1

Network

- Polycom iPriority™ for QoS
- 10/100/1000 auto NIC (RJ45)
- H.323 and/or SIP up to 2 Mbps
- Polycom Lost Packet Recovery™ (LPR™)
- Reconfigurable MTU size (IP only)
- Microsoft® Office Communications Server 2007 integration
- Microsoft® ICE support

User Interface

- Directory services
- System management
 - Web-based
 - SNMP
 - Polycom Converged Management Application™ (CMA™)
- CDR
- International languages (17)
- Wildcard language tool
- USB software update

Security

- Secure Web
- Security mode
- AES FIPS 197, H.235V3 and H.233/234
- FIPS 140-2 Validation Certificate (#918)
- IPv6 (DISA)
- www.polycom.com/govcerts
- Secure password authentication

Options

- IP 7000 speakerphone integration
- HDX Media Center options

Electrical

- Auto sensing power supply
- Typical operating voltage/power
 - 189VA @ 115V @ 60 Hz @ .67 PF
 - 192VA @ 230V @ 60 Hz @ .66 PF
 - 196VA @ 230V @ 50 Hz @ .65 PF

Environmental Specification

- Operating temperature: 0—40°C
- Operating humidity: 10—80%
- Non-operating temperature: 40°—70°C
- Non-operating humidity (non-condensing): 10—90%
- Maximum altitude: 10,000 feet

Physical Characteristics

- HDX 6000 base box with removable stand
 - 13.9" x 5.1" x 11" (H/W/D standing)

Warranty

- One-year return to factory parts and labor

Polycom Worldwide Headquarters
4750 Willow Road, Pleasanton, CA 94588
1.800.POLYCOM or +1.925.924.6000
www.polycom.com

